

NO	1	2010 EDITION	DESCRIPTION OF REVISIONS	MADE BY	DATE	NO	3	4	DESCRIPTION OF REVISIONS	MADE BY	DATE
				C. COLE	03/10						

NOTES:

1. Except where otherwise noted, all dimensions shall have a ±0.0625 inch tolerance.
2. Ventilation louvers with filter/shell assembly shall be provided on rear door of cabinet.
3. Hinges for the rear cabinet door shall be located on the left side when facing the rear of the cabinet.
4. See plan sheets for seven digit cabinet identification code. Numbers shall be placed in such a manner that the entire seven digit cabinet identification code is centered horizontally in the cabinet's back door and on the side of the cabinet facing traffic.
5. All AC neutral circuits in cabinet shall be connected to the cabinet ground rod via a bare AWG #8 solid copper wire from one of the neutral buses.
6. See Special Provisions for Specific Requirements for this cabinet and its components.
7. See foundation requirements, per T.S. 2 Series.

NOT TO SCALE

DESIGN APPROVED	ARIZONA DEPARTMENT OF TRANSPORTATION INTERMODAL TRANSPORTATION DIVISION TRAFFIC SIGNALS AND LIGHTING STANDARD DRAWINGS	REVISION	03/10
SIGNATURE		DRAWING NO.	T.S. 3-13
APPROVED FOR DISTRIBUTION	TRAFFIC SIGNALS AND LIGHTING MODEL 345 CABINET DETAILS	SHEET NO.	2 OF 3
ON FILE			