

(A) ITEM - ASPHALTIC CONCRETE (MISCELLANEOUS STRUCTURAL)

The asphaltic concrete shall be as specified in Section 409 of the Standard Specifications, and Contracts and Specifications Stored Spec. "409ACMS".

For estimating purposes the unit weight of the bituminous mix is * pounds per cubic foot.

The asphalt cement type shall be PG *.

The estimated haul distance for the asphaltic concrete is ** miles.

On a project by project basis, Item # 109a [Pavement Smoothness (AC)] must also be included in the Materials Design Report.

**(B) ITEM - ASPHALTIC CONCRETE
(MISCELLANEOUS STRUCTURAL - SPECIAL MIX)**

The asphaltic concrete shall be as specified in Section 409 of the Standard Specifications, and Contracts and Specifications Stored Spec. "409AGGR".

For estimating purposes the unit weight of the bituminous mix is * pounds per cubic foot.

The asphalt cement type shall be PG *.

The estimated haul distance for the asphaltic concrete is ** miles.

On a project by project basis, Item # 109a [Pavement Smoothness (AC)] must also be included in the Materials Design Report.

DESIGNER:

The Bituminous Engineer should be contacted to determine which Item to use on a particular project.

The AC (Misc. Structural) and AC (Misc. Structural – Special Mix) items are generally used for structural purposes and when the quantity is less than 4,500 Tons.

For asphaltic concrete quantities less than 200 tons and to be used for nonstructural purposes, see Item # 406a – Asphaltic Concrete (Misc. Paving).

* To be supplied by the Bituminous Engineer.

** To be supplied by Geotechnical Services.