

A, B, C and D equal spaces are measured along slope (8 feet maximum vertical and 15 feet maximum horizontal). Project Plans shall show site specific layout, dimensions and slope of the paving at bridge abutments.

Redwood dividers (Typ)

Exposed Aggregate (Typ)

Front face of abutment



Construction Specification - Arizona Department  
of Transportation Standard Specifications for  
Road and Bridge Construction, latest Edition.

Concrete for slope paving shall be Class "S",  
(f'c = 3000 psi) with exposed aggregate surface.  
Maximum size coarse aggregate shall be 3/4 inch.

Welded Wire Reinforcement 6 x 6 - W2.5 x W2.5 shall conform to ASTM A1064.

Slope Paving work will be paid for under its respective Contract Item.



STANDARDS ENGINEER <div style="text-align: center;">A. ALZUBI</div>	ARIZONA DEPARTMENT OF TRANSPORTATION INFRASTRUCTURE DELIVERY AND OPERATIONS DIVISION <b>BRIDGE GROUP STANDARD DRAWING</b>	
RECOMMENDED FOR APPROVAL GROUP MANAGER <div style="text-align: center;">D. BENTON</div>		
APPROVED <div style="text-align: right;">08/23</div>	SLOPE PAVING DETAILS	DRAWING NO.  SD 2.04
STANDARDS COMMITTEE APPROVED FOR DISTRIBUTION <div style="text-align: right;">DATE</div>		

**Note to Designer:** The information presented in this Standard Drawing has been prepared in accordance with recognized engineering principles and is for general use. It should not be used for specific application without the competent professional examination and verification of its suitability and applicability by a licensed professional engineer. Contents within the inner border line shall not be altered.

PRIOR DISTRIBUTION DATE	12/07
-------------------------	-------