

**1325 CULVERT PIPE THICKNESS**

CORRUGATED GALVANIZED STEEL (Class 1, Zinc or Aluminum Coated)

GAUGE NO.	THICKNESS		MINIMUM THICKNESS				KILOGRAMS / m <sup>2</sup> OF BASE MATERIAL	OUNCES / SQ. FT. OF BASE MATERIAL
	mm	in.	PIPE mm	PIPE in.	PIPEPLATE mm	PIPEPLATE in.		
	0.71	0.028	0.61	0.024				
22	0.86	0.034	0.76	0.030				
20	1.02	0.040	0.91	0.036			7.32	24
18	1.32	0.052	1.17	0.046			9.76	32
16	1.63	0.064	1.45	0.057			12.21	40
14	2.01	0.079	1.83	0.072			15.26	50
12	2.77	0.109	2.57	0.101	2.46	0.097	21.36	70
10	3.51	0.138	3.28	0.129	3.20	0.126	27.46	90
8	4.27	0.168	4.04	0.159	3.96	0.156	33.57	110
7	4.78	0.188			4.47	0.176	36.62	120
5	5.54	0.218			5.23	0.206	42.72	140
3	6.32	0.249			6.02	0.237	48.82	160
1	7.11	0.280			6.81	0.268	54.93	180