

CRUMB RUBBER ASPHALT TEST DATA

WHITE
 YELLOW
 BLUE

| | | |
|----------------|-------------------|-------------|
| IDENT | C R A - | SAMPLE DATE |
| SAMPLED BY | POINT OF SAMPLING | QUANTITY |
| SUPPLIER | | REMARKS |
| PROJECT NUMBER | TRACS NO. | RECEIVED |
| COMMENCED | LAB NUMBER | |

| | | | SPEC | | |
|---|---|-------------------------|------|-------------------------|--|
| TEST | RESULT | MIN | | MAX | |
| Rotational Viscosity at 177°C (350°F) | <input type="text"/> Pa.s | | | | |
| Cone Penetration at 25°C (77°F) (ASTM D5329) | <input type="text"/> | | | | |
| Penetration at 4°C (39.2°F) (ASTM D5) | <input type="text"/> | | | | |
| Softening Point (ASTM D36) | <input type="text"/> °C <input type="text"/> °F | <input type="text"/> °C | | <input type="text"/> °F | |
| Resilience at 25°C (77°F) (ASTM D5329) | <input type="text"/> % | | | | |
| Specific Gravity (AASHTO T228) | <input type="text"/> | | | | |

REMARKS:

LAB SUPERVISOR _____ DATE _____